

Web Images Videos Maps News Shopping Gmail more ▾

Sign in

Google scholar

tag data structure

Search

Advanced Scholar Search
Scholar Preferences

Scholar

Articles and patents ▾

anytime ▾

include citations ▾



Create email alert Results

ANN: A library for approximate nearest neighbor searching

DM Mount, S Arya - CGC 2nd Annual Fall Workshop on Computational ..., 1997 - Citeseer

... Add a **tag**: BibTeX | Add To MetaCart. ... In nearest neighbor searching, we are given a set of **data** points S in real d -dimensional space, \mathbb{R}^d , and are to build a **data structure** such that, given any query point $q \in \mathbb{R}^d$, the nearest **data** point to q can be found efficiently. ...

Cited by 142 - Related articles - Cached - All 3 versions

Garbage collection in an uncooperative environment

HJ Boehm, M Weiser - Software: practice and Experience, 1968 - interscience.wiley.com

... Normally this is accomplished by maintaining **tags**. ... In more ambitious systems the user program may be required to maintain reference counts, or even to update marks used to determine the accessibility of **data structures**. We wanted to avoid the need for such co-operation, for ...

Cited by 598 - Related articles - All 13 versions

Type extensions

N Wirth - ACM Transactions on Programming Languages and ..., 1968 - portal.acm.org

... 5. EXTENDED TYPES VERSUS VARIANT RECORDS Inhomogeneous **data structures** are quite common. Most languages offer some facility to express these **structures** in tricky and, from a ... a field declared as belonging to one category, whereas actually the **tag** value specifies ...

Cited by 146 - Related articles - All 12 versions

Sequence **tag** identification of intact proteins by matching tandem mass spectral **data** against sequence **data** bases

E Mørtz, PB O'Connor, P Roepstorff, ... - Proceedings of the ..., 1996 - National Acad Sciences

... The N-terminal part of the protein sequence **tag** (region 1) showed a mass 130.6 Da below that expected from the **data** base sequence ... showed the same mass shift within 0.3 Da to confirm the missing N-terminal Met; 10 Y⁺ ions also confirmed (± 0.2 Da) this primary **structure**. ...

Cited by 119 - Related articles - BL Direct - All 9 versions

Identification, characterization, and crystal **structure** of the Omega class glutathione transferases

PG Board, M Coggan, G Chelvanayagam, S ... - Journal of Biological ..., 2000 - ASBMB

... A new class of glutathione transferases has been discovered by analysis of the expressed sequence **tag data** base and sequence alignment. ... The **structure** of GSTO 1-1 has been determined at 2.0-Å resolution and has a characteristic GST fold (Protein **Data** Bank entry code ...

Cited by 344 - Related articles - BL Direct - All 10 versions

[CITATION] **Data structures** using C

AM Tenenbaum - Pearson Education India

Cited by 201 - Related articles - Library Search - All 4 versions

LH*—a scalable, distributed **data structure**

W Litwin, MA Neimat, DA Schneider - ACM Transactions on ..., 1996 - portal.acm.org

... We present a scalable distributed **data structure** called LH*. LH* generalizes Linear Hashing (LH) to distributed RAM and disk files. ... LH*—A Scalable, Distributed **Data Structure** • 481 ACM Transactions on Database Systems, Vol. 21, No. 4, December 1996. Page 3. ...

Cited by 231 - Related articles - BL Direct - All 17 versions

[BOOK] The design of dynamic data structuresMH Overmars - 1983 - books.google.com

... The complexity of such a **data structure** is measured by three bounds: the building time, the amount of storage required to store the **structure** and the query time, ie, the amount of time required for answering a question on it. In ...

[Cited by 279](#) - [Related articles](#) - [Library Search](#) - [All 4 versions](#)

[PDF] Mach: A new kernel foundation for UNIX developmentM Accetta, R Baron, W Bolosky, D Golub, R Rashid, A ... - [contract](#) - [Citeseer](#)

... The Mach interprocess communication facility is defined in terms of ports and messages and provides both location independence, security and **data type tag**-ging. 9 Page 10. ... Ports are used by tasks to represent services or **data structures**. ...

[Cited by 1256](#) - [Related articles](#) - [View as HTML](#) - [All 30 versions](#)

R: A language for data analysis and graphicsR Ihaka, R Gentleman - [Journal of computational and graphical statistics](#), 1996 - [JSTOR](#)

... The **data structure** consists of five machine words. The first of these is a **tag** that contains type information and some miscellaneous bit-fields that are used for internal purposes. The second word contains a (possibly null) pointer that is used to attach a list of attributes to objects. ...

[Cited by 5063](#) - [Related articles](#) - [BL Direct](#) - [All 6 versions](#)

 [Create email alert](#)



Result Page: **Previous** [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [11](#) [12](#) [13](#) **Next**

[Go to Google Home](#) - [About Google](#) - [About Google Scholar](#)

©2010 Google